



Y-block, X-block

Assembly Instructions
© Nuke Performance AB 2010

For more information visit:
www.nukeperformance.com

- 1** 3 / 4 UNF-AN8 Fitting
- 2** O-Ring 19,1 * 1,6 mm
- 3** Y-Block
Thread 3 / 4 UNF

Product information

For more info contact your local retailer.

For use on turbo-charged, super-charged and Naturally aspirated engine applications.

Designed to stand up to the destructive properties of alcohol fuels, including methanol and ethanol.

The body and all components are CNC-machined from 6082 aluminum alloy.

The design of the y-fitting and x-fittings gives a very clean and High performance appearance.

It's available in blue or black finish.

Technical information

For more info contact your local retailer.

CNC manufactured from aluminium alloy 6082.

Available with either two (Y) or three (X) output ports.

The thread is 3 / 4 UNF.
Delivered with two dash 8 and one dash 10.



This product is designed, developed and manufactured by Nuke Performance AB in Sweden.

Use Lubricant before tightening fittings and always use extra care when handling any kind of fuel.

All our products are installed at your own risk and could damage your equipment, engine or vehicle, unless they are properly installed.

Information:

Design combined with top quality performance.

For more information about the products and retailers visit

www.nukeperformance.com

nuke
PERFORMANCE