



AN / Hose ends

Assembly Instructions

© Nuke Performance AB 2010

For more information visit:

www.nukeperformance.com

- | | |
|--|------------------------------|
| 1 Aluminium tube | 5 Seals the hose |
| 2 Laser welding | 6 Holds hose in place |
| 3 O-Ring | 7 Seals AN Fittings |
| 4 Pins
Pressed in after assembly | |

Product information

For more info contact your local retailer.

For use on turbo-charged, super-charged and Naturally aspirated engine applications.

The body and all components are CNC-machined from 6082 aluminum alloy.

The Hose ends is Hard anodised for a long lasting, corrosion-free appearance.

Designed to stand up to the destructive properties of alcohol fuels, including methanol and ethanol.

Productline is AN-4/6/8/10/12 Straight, 45, 90 and 180 degrees.

Technical information

For more info contact your local retailer.

Aluminium extrusion 6082.

Is available in AN4, AN6, AN8, AN10 and AN12.

All sizes is available in Straight, 45, 90 and 180degrees.

Hard anodised, resist higher amount of wear and corrosion resistance then competing manufacturers.



This product is designed, developed and manufactured by Nuke Performance AB in Sweden.

Use Lubricant before tightening fittings and allways use extra care when handling any kind of fuel.

All our products are installed at your own risk and could damage your equipment, engine or vehicle, unless they are properly installed.

Information:

Design combined with top quality performance.

For more information about the products and retailers visit

www.nukeperformance.com

nuke
PERFORMANCE